

Indoor unit model name SRK25ZSX-S Outdoor unit model name SRC25ZSX-S

| Refrigerant | R410A | GWP | 1 | 975 | |
|---------------------------------------------------------------|-------------------------------------------------------------------------------------------------|----------------------------------------------|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| contribute less to contains a refrige leaked to the atm | global warming than rant fluid with a GWF osphere, the impact rrs. Never try to interf | a refrigerant equal to 19 on global wa | t with h 75. Thi irming v | erant with lower global warming po gher GWP, if leaked to the atmos s means that if 1kg of this refrigera yould be 1975 times higher than 1 ant circuit yourself or disassemble | phere. This appliance ant fluid would be kg of CO2, over a |
| Cooling mode | | | | | |
| SEER | | 9.6 | | | |
| Energy efficie | | A+++ | 1.1.1/ | | |
| Design load (F | | | kW | per veer beend op standard | toot rooulto |
| Energy consu Actual energ | | | | per year.based on standard ne appliance is used and when | |
| Heating mode (A | verage) | | | | |
| SCOP | | 5.2 | | | |
| Energy efficie | | A+++ | | | |
| Design load (F | | | kW | (-10°C) | |
| Declared capa | | 2.90 | | (-10°C) | |
| Back up heati | | | kW | (-10°C) | 1 |
| Energy consu Actual energ | | | | per year.based on standard ne appliance is used and wher | |
| Heating mode (W | /armer) Optional | | | | |
| SCOP | | 6.6 | | | |
| Energy efficie | 3 | A+++ | | | |
| Design load (F | | | kW | (2°C) | |
| Declared capa | | 4.10 | | (2°C) | |
| Back up heati | | | kW | (2°C) | toot rooulto |
| Energy consu Actual energ | | | | per year.based on standard ne appliance is used and when | |
| Heating mode (C | older) Optional | | | | |
| SCOP | | - | | | |
| Energy efficie | 3 | - | | | |
| Design load (F | | | kW | (-22°C) | |
| Declared capa | , | | kW | (-22°C) | |
| Back up heati | | | kW | (-22°C) | 4 4 |
| Energy consu | | | | per year.based on standard | |
| | gy consumption will | aepend on | now t | ne appliance is used and when | e it is located. |
| Actual energ | | | | | |
| Sound power | level (indoor) | 55 | | dB(A) | |
| Sound power | level (indoor) level (outdoor) | 55 57 | | dB(A) dB(A) | |