

Indoor unit model name SRK35ZSX-S Outdoor unit model name SRC35ZSX-S

Refrigerant	R410A	GWP	1	975	
contribute less to contains a refrige leaked to the atm	global warming than rant fluid with a GWF osphere, the impact rrs. Never try to interf	a refrigerant equal to 19 on global wa	t with h 75. Thi rming v	igher GWP, if leake s means that if 1kg would be 1975 time	bal warming potential (GWP) would ed to the atmosphere. This appliance of this refrigerant fluid would be s higher than 1kg of CO2, over a or disassemble the product yourself
Cooling mode					
SEER		9.2			
Energy efficie		A+++			
Design load (I			kW		
Energy consu Actual energ					on standard test results. sed and where it is located.
Heating mode (A SCOP	verage)	5.1			
Energy efficie	ncy class	A+++			
Design load (F	5		kW	(-10°C)	
Declared capa		3.30		(-10°C)	
Back up heati			kW	(-10°C)	
Energy consu					on standard test results.
					sed and where it is located.
Heating mode (W	/armer) Optional				
SCOP		6.5			
Energy efficie		A+++			
Design load (F			kW	(2°C)	
Declared capa		4.60		(2°C)	
Back up heati			kW	(2°C)	
Energy consu					on standard test results.
Actual energ	y consumption will	depend on	how t	he appliance is u	sed and where it is located.
Heating mode (C	older) Optional				
SCOP	<i>,</i> .	-			
Energy efficie	ncy class	-			
Design load (F			kW	(-22°C)	
Declared capa	acity		kW	(-22°C)	
Back up heati	ng capacity	-	kW	(-22°C)	
Energy consu					on standard test results.
Actual energ	y consumption will				sed and where it is located.
Sound power	level (indoor)	58		dB(A)	
				· · ·	
	level (outdoor)	61		dB(A)	